

RHINO 4T RACING MOTOR OIL SAE 10W40 API SN/CF JASO MA

Premium Synthetic Blend 4-Stroke Motor Oil

DESCRIPTION

RHINO 4T RACING MOTOR OIL SAE 10W40 API SN/CF JASO MA is a synthetic technology superior performance premium engine oil formulated with the latest additive technology including *FULL ZINC +(exceeding 1800+ ppm levels) for maximum engine, gearbox & clutch protection against wear, corrosion, oil oxidation, piston deposits and sludge under all conditions. It exceeds the requirements of API SN/CF and JASO MA.

APPLICATIONS

RHINO 4T RACING MOTOR OIL SAE 10W40 API SN/CF JASO MA is designed for use in modern four stroke road & sports bikes, dirt & enduro bikes, ATV's/Quad bikes and 4 stroke scooters that require a synthetic engine oil. It is especially suited to medium and large capacity V Twin and opposed cylinder engines. It can also be used in transmissions with dry or wet clutch systems or where engine & gearbox oils are combined. It has optimum clutch slip prevention in these systems and exceeds JASO MA requirements. Also suitable for use in other four stroke engines such as stationary engines & generators or vehicles that require this grade and specification of engine oil and can be used with most petrol, racing & other conventional fuels.

PROPERTIES

RHINO 4T RACING MOTOR OIL SAE 10W40 API SN/CF JASO MA provides superior oil film strength, heat resistance and oil shear protection. It provides superior oil film strength and heat resistance for the protection of engine compression & oil sealing rings, cylinder sleeve lubrication, bearing and valve train. Viscosity fluctuations with temperature variations are minimal, thus creating less friction in the engine. This enhances the power-output and fuel economy of your race bike. This oil easily resists high temperatures and reduces deposits.

PERFORMANCE FEATURES AND BENEFITS

- Maximum wear protection
- Minimum sludge formation & reduced piston deposits
- FULL ZINC + anti-wear additive package for ultimate engine wear protection
- MAXIMUM power and acceleration
- Optimum lubrication at cold start
- Suitable for wet clutch systems
- Trusted protection for performance engines
- LATEST oil technology for less wear, sludge & piston deposits
- Extends engine life by reducing formation of high temperature engine deposits
- Very high temperature stability

RECOMMENDATIONS / SPECIFICATIONS

API SN, SN/CF, SM, SL, SH, SG, JASO MA, MA 2

Recommended for vehicles such as Aprilia, BMW, Honda, Kawasaki, KTM, Moto Guzzi, Suzuki, V Moto, Yamaha, Cagiva, Can-Am, Ducati, Hyosung, Triumph and more

TYPICAL TECHNICAL PROPERTIES

	4T MOTOR OIL
PRODUCT CODE:	SEO-25010-4T
ISO Viscosity Grade	10W40
Density at 15°C, g/ml, ASTM D4052	0.860
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	5050@-25°C
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	97.5
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	15.15
Viscosity Index, ASTM D2270	164
Flash Point(COC), °C, ASTM D92	228
Pour Point, °C, ASTM D97	-36
Total Base Number, mg KOH/g, ASTM D2896	8.4

Note: These characteristics are typical of current production. While future production will conform to RHINO's specification, variations in these characteristics may occur.
R/PDS/AL/013-12446AL/02*, 01.06.25, Page 1/1
* supersedes all previous versions

Packing: 700 ml, 800 ml, 1L, 2L, 3L, 4L, 5L, 18L, 20L, 25L, 200L, 205L, 208L, 210L