

RHINO

ULTRA FULLY SYNTHETIC ENGINE OIL SAE 0W-30 SN C3 LL

(Fully synthetic motor oil - Strength for Maximum Performance)

DESCRIPTION

RHINO ULTRA FULLY SYNTHETIC ENGINE OIL SAE 0W-30 API SN C3 LL is a full synthetic lubricant based on carefully selected very high-quality base oils. It is specifically formulated to meet the most demanding VW specifications available today – VW 504.00 and 507.00 – as well as the Long-Life III requirements of the VAG Group. It is a Mid SAPS oil which meets Euro 4 and Euro 5 norms and provides protection to the Diesel Particulate Filter. This viscosity grade provides a proven fuel economy over a 5W30 grade.

APPLICATIONS

- RHINO ULTRA FULLY SYNTHETIC ENGINE OIL SAE 0W-30 SN C3 LL** is suitable for cars, gasoline, and diesel engines where the maker suggests an ACEA C3 specification 0W-30 lubricant.
- It is backward compatible: 504.00 and 507.00 supersedes all previous VW specifications (502.00, 503.00, 503.01, 505.00, 506.00, and 506.01).
- Suitable for all VAG Group vehicles (Volkswagen, Audi, Seat, and Skoda) with extended oil change intervals (30,000 km or 2 years) from 2007 onward.
- Note: We don't recommend this oil for V10 TDI and 5-cylinder 2.5 TDI engines made before 2007 that require the 506.01 specification.
- For first-generation engines with pump injector units, use the 505.01 specification oil.



PERFORMANCE FEATURES AND BENEFITS

- Complete engine protection and Keep the engine clean for optimal performance.
- Fuel economy: superior fuel economy and CO2 reduction
- Cold start: excellent fluidity at low temperature

RECOMMENDATIONS / SPECIFICATIONS

International Standards:

API SN, ACEA C2, C3

Meets or exceeds:

MB 229.51/52, 229.31, Porsche C30,
VW 504 00/ 507 00/ VW TL 52 545,
BMW Long-life 04, RN 0700/0710,
FIAT 9.55535-DS1/9.55535-GS1, FIAT 9.55535-S3

TYPICAL TECHNICAL PROPERTIES

Viscosity Grade, SAE J300	0W-30
PRODUCT CODE	PCMO-24017
Density at 15°C, g/ml, ASTM D4052	0.842
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	5700 @-35°C
Kinematic Viscosity at 40°C, mm²/s, ASTM D445	59.0
Kinematic Viscosity at 100°C, mm²/s, ASTM D445	11.7
Viscosity Index, ASTM D2270	197
Flash Point(COC), °C , ASTM D92	226
Pour Point, °C , ASTM D97	-45
Total Base Number (TBN), mg KOH/g, ASTM D2896	8.3

Note: The information contained herein is subject to change without notification.
Typical Properties may vary slightly.

R/PDS/AL/027A-160701INF-01-6080/03*, 12.11.25, Page 1/1

* Supersedes all previous version

Packing: 1L, 5L, 20L, 60L, 200L

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment.