

RHINO

SYNTECH ENGINE OIL SAE 10W-40 API SN/CF A3/B4

(Fully Synthetic Motor Oils – Full SAPs)

DESCRIPTION

RHINO SYNTECH ENGINE OIL SAE 10W-40 API SN/CF A3/B4

is premium performance synthetic motor oil delivering ultimate performance and protection. It provides exceptional cleaning power, wear protection and overall performance keeping your engine running like new in all driving conditions.

APPLICATIONS

RHINO SYNTECH ENGINE OIL SAE 10W-40 API SN/CF A3/B4

is top-tier motor oils recommended for many types of modern vehicles where it will help provide unsurpassed performance even under very demanding driving conditions. Extensive cooperative development work with major manufacturers and the application of the latest lubrication technology make them suitable for the latest engine technologies including Turbo-chargers, Direct Injection, Diesels (without DPF) and Hybrids, High performance engines

RECOMMENDATIONS / SPECIFICATIONS

International Standards:

API SN/CF, ACEA: A3/B3, A3/B4

Meets or exceeds:

MB 229.3, MB 229.1, MB 226.5, MB 229.5, Opel GM-LL-B-025, Porsche A40, JASO MA2, PSA B71 2300, RN0700/0710, VW 50200/50500

Check owners' manual before use

TYPICAL TECHNICAL PROPERTIES

Viscosity Grade, SAE J300	10W-40
PRODUCT CODE	PCMO-24113
Density at 15°C, g/ml, ASTM D4052	0.855
Cold Cranking Viscosity(CCS), mPa s, ASTM D5293	6430 @-25°C
Kinematic Viscosity at 40°C, mm²/s, ASTM D445	86.12
Kinematic Viscosity at 100°C, mm²/s, ASTM D445	14.2
Viscosity Index, ASTM D2270	171
Flash Point(COC), ° C, ASTM D92	228
Pour Point, ° C, ASTM D97	-39
Total Base Number (TBN), mg KOH/g, ASTM D2896	10.1
Sulphated Ash, %wt, ASTM D874	0.98

Note: The information contained herein is subject to change without notification.

Typical Properties may vary slightly.



PERFORMANCE FEATURES AND BENEFITS

- Total engine protection: performance in keeping the engine clean
- Cold start: excellent fluidity at low temperature
- Drain interval extension: longer oil drain interval

PROPERTIES

RHINO SYNTECH ENGINE OIL SAE 10W-40

API SN/CF A3/B4 is high performance engine oils specifically developed to provide the highest fuel economy and lowest CO2 emissions. These result from laboratory synthesis of precisely controlled ingredients created by oil engineers, scientists and chemists. When combined with a high-performance additive package, this results in an oil with the highest levels of lubrication and engine protection, generally offering better protection at startup, better cleansing qualities, enhanced durability and better protection against heat buildup.

R/PDS/AL/02.1B-012330HT/02*, 12.11.25, Page 1/1

* Supersedes all previous version

Packing: 1L, 5L, 20L, 60L, 200L

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment.